

AET Lézaud GmbH, Am Hottenwald 8, 66606 St. Wendel

☎ +49 (0)6851/97394 0 📠 +49 (0)6851/97394 44 ✉ industrie@lezaud.de 🌐 www.lezaud.de

Technical data sheet Status: 01.06.2021

Plug / Septa

LEZ-GOM Serie F

Pos	Parameter	Value	Unit	Norm
	Elastomer base	NR		
	Geometry	Stoppers		
	Density	1,28	g/cm ³	DIN 53479
	Hardness	40 +/-5	Shore A	DIN 53505
	Tensile strength	7,1	N/mm ²	DIN 53504
	Impact elasticity	38	%	DIN 53512
	Elongation	844	%	DIN 53504
	Compression set	26,5 at 70°C; 24 h	MPa	DIN 53504
	Temperature	-40 to +80	°C	
	Color	grey		

Pos*	Compliant	Addition
S1	BfR XXI Kat.2	

Pos* A= Outside; IN= Inside, S1= Side1,,S2= Side2

The values of these specifications come from regular controls of the compounds with the aid of norm samples and perform an average. They correspond to the actual state of the knowledge, the latest development of the sciences and our experience. They do not specify sure properties for the finals products. The indications in this data sheet are only a description of the typical properties and represent an aid and information for the user to give him some suggestions for his own application. But it remains in his responsibility to make sure with a specific trial that our product suits for his own purpose.

We strive to continuously improve our products. We reserve the right to modify and adjust the data sheet and our blends referring to the material properties. These will be documented with a new change status (date).