

AET Lézaud GmbH, Am Hottenwald 8, 66606 St. Wendel

☎ +49 (0)6851/97394 0 📠 +49 (0)6851/97394 44 ✉ industrie@lezaud.de 🌐 www.lezaud.de

Technical data sheet Status: 01.06.2021

Accessories

LEZ-SILFIX 732

Pos	Parameter	Value	Unit	Norm
	Elastomer base	Silicone		
		Glue		
	Specific weight	1,04		ASTM D1457
	Durometer-hardness	25	Shore A	ASTM D2240
	Tensile strength	2,3	MPa	ASTM D412
	Elongation at break	540	%	ASTM D412
	Temperature	-60 to +180	°C	
	Color	transparent		
Pos*	Compliant	Addition		
	FDA 21 CFR §177 2600			

Pos* A= Outside; IN= Inside, S1= Side1; S2= Side2

The values of these specifications come from regular controls of the compounds with the aid of norm samples and perform an average. They correspond to the actual state of the knowledge, the latest development of the sciences and our experience. They do not specify sure properties for the final products. The indications in this data sheet are only a description of the typical properties and represent an aid and information for the user to give him some suggestions for his own application. But it remains in his responsibility to make sure with a specific trial that our product suits for his own purpose.

We strive to continuously improve our products. We reserve the right to modify and adjust the data sheet and our blends referring to the material properties. These will be documented with a new change status (date).